

Single Phase I High Speed

Mini Pressure Boosting System

► SMPBS



*Available in X series

| Parameters | Range |
|---------------|---------------------|
| Power Rating | 0.5 hp |
| Pressure Flow | 1 - 2.5 Bar |
| Flow Rate | 2 m ³ /h |
| Pipe Size | 25 X 25 mm |
| Voltage | 240 V (-15% to +6%) |
| Speed | 2800 rpm |




SALIENT FEATURES

- Energy efficient hydraulic & electric design
- TEFC construction, specifically designed for pressure boosting system
- High quality branded pressure switch & tank for longer life
- Rigid construction for noiseless operation & vibration free running
- Ease of installation & compact design
- TEFC, AC induction motor with "F" class winding for continuous operations

APPLICATIONS



Flood water pumping



Bathrooms, Kitchen & Water wash



Pressurized water supply to gardens, Sprayers



Irrigation & water wash applications

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045. Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice