

Single Phase

# Centrifugal Shallow Well Jet Monobloc Pumpset



- ▶ SHCS-SJ
- ▶ SHCS-SJC

\*Available in X series

Parameters	Range
Power Rating	0.5 - 1.0 hp
Head Range	6 - 36 m
Discharge Range	10 - 45 lpm
Voltage	230 V (-15% to +6%)
Speed	2850 rpm



## SALIENT FEATURES

- In-built jet
- Single phase TEFC construction
- Carbon vs Ceramic mechanical seal
- High efficiency with wide operating range
- Available in cast iron and stainless steel delivery chamber




## OPERATING CONDITIONS

- Liquid temperature up to 60°C
- Ambient temperature up to 60°C
- Total suction head up to 7 mtrs continuous duty

## APPLICATIONS



Small farms,  
Lawns and gardens



Pressure boosting  
system



Domestic water supply,  
residential bungalows



Fountains, Lawns and  
Gardens

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

**SAMUDRA PUMPS (INDIA) PVT LTD**

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore - 641 045, Tamilnadu, India

E-Mail: [info@samudrapumps.com](mailto:info@samudrapumps.com) | +91 422 498 2255