

Single Phase

# Submersible Sewage Pump

► SWP 7050 S



Parameters	Range
Power Rating	1.0 hp
Head Range	4 - 12 m
Discharge Range	67 - 330 lpm
Voltage	230 V (-15% to +6%)
Speed	2850 rpm
Protection	IP68
Insulation	Class F

## SALIENT FEATURES

- Dry type submersible induction motor
- Built in capacitor run, "F" class insulation motor
- Fasteners, shaft & clamps AISI 304 materials
- Casing, impeller and other casting are, FG 260 grade & CED coated to improve life and performance
- Carbon / ceramic dual mechanical seal prevents water entry into the dry motor portion
- SS sand guard
- Open type impeller for non- clogging operation
- Can handle particle size up to 25 mm
- SS sand guard


## APPLICATIONS



Flood water pumping



Dewatering for basement, underground parking's, garages



Waste water from multi-storey building, residential, hotels



Slushy, water, waste water without solids

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

**SAMUDRA PUMPS (INDIA) PVT LTD**

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045. Tamilnadu, India

E-Mail: [info@samudrapumps.com](mailto:info@samudrapumps.com) | +91 422 498 2255