

Single Phase

Vertical Submersible Pumpset



► SVS

*Available in X series

Parameters	Range
Power Rating	1.0 - 1.5 hp
Head Range	13 - 78 m
Discharge Range	30 - 180 lpm
Voltage	220 V (-15% to +6%)
Speed	2850 rpm

SALIENT FEATURES

- Easy installation & foundation not required
- Improved efficient and reduced power consumption
- Impellers and diffusers of high quality water portable engineering polymer
- Motor & pump is coupled with a slide coupling for easy serviceability
- Easy rewindable squirrel cage motor designed to operate in a wide range of voltage variation 180 - 240 V, 50 Hz power supply
- Pre - filled with special anti-corrosive solution to protect internal parts of motor from corrosion
- CED coated cast iron components for long lasting corrosion protection
- Special mounting stands are provided for placing the sets in horizontal position



OPERATING CONDITIONS

- Single Phase, 180 - 240V, 50Hz, AC power supply
- Clear cold water with a maximum sand content of 50grams in 1000 ml
- Protect to be earthed properly to avoid malfunction

APPLICATIONS




Sump and water tanks



Domestic water supply in apartments



Building and hotels



Gardening and irrigation

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore - 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255