

Three Phase I Radial Flow

Ultra Head Borewell Submersible Pumpset (160 mm)



► SRS UH

*Available in X, NX series

Parameters	Range
Power Rating	5.0 - 25 hp
Head Range	25 - 358 m
Discharge Range	30 - 450 lpm
Voltage	415 V (-15% to +6%)
Speed	2850 rpm

SALIENT FEATURES

- Energy efficient motors and pumps
- Wide operating voltage brand
- All casting are in superior FG 260 grade
- Heavy duty journal and tilting thrust bearings
- Optimized diaphragm design
- Motor filled with anti-corrosive solution
- Easy serviceability
- Three layer protection to avoid sand entry into motor
- Pump bearing bush made up nitrile for better wear resistance
- Diffuser is made of IC casing CF grade & impeller is in CA 15 CA 40 grade steel

APPLICATIONS



Open, Sprinkler, Drip
and lift Irrigation



large multistoried
apartments



Industrial water
supply



Pressure boosting
system



In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255