

Three Phase I Mixed Flow

Borewell Submersible Pumpset (175 mm)



► SMVS

Parameters	Range
Power Rating	6 - 15 hp
Head Range	4.8 - 64 m
Discharge Range	10 - 32 lps
Voltage	415 V (-15% to +6%)
Speed	2850 rpm
Delivery Pipe Size	100 mm

SALIENT FEATURES

- Energy efficient motors and pumps
- Wide operating voltage brand
- All casting are in superior FG 260 grade
- Heavy duty journal and tilting thrust bearings
- Optimized diaphragm design
- Motor filled with anti-corrosive solution
- Easy serviceability
- Three layer protection to avoid sand entry into motor
- Each stage of pump is fitted with sand resisting rubber / rubber clad metal bushes & wear rings



In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

APPLICATIONS



Open, Sprinkler, Drip and lift Irrigation



large multistoried apartments



Industrial water supply



Individual residences

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore - 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255