

Three Phase I Radial Flow

Borewell Submersible Pumpset (200 mm)



► SRE-NX

Parameters	Range
Power Rating	25.0 - 60 hp
Head Range	76 - 473 m
Discharge Range	120 - 900 lpm
Voltage	415 V (-15% to +6%)
Speed	2850 rpm
Delivery Pipe Size	80 mm

SALIENT FEATURES

- Energy efficient motors and pumps
- Wide operating voltage brand
- All casting are in superior FG 260 grade
- Heavy duty journal and tilting thrust bearings
- Optimized diaphragm design
- Motor filled with anti-corrosive solution
- Easy serviceability
- Three layer protection to avoid sand entry into motor
- Pump bearing bush made up of nitrile for better wear resistance
- Diffuser is made of IC casing CF grade & impeller is in CA 15, CA 40 grade steel



In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

APPLICATIONS



Open, Sprinkler, Drip and lift Irrigation



large multistoried apartments



Industrial water supply



Individual residences

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore - 641 045. Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255