

Samudra Platinum uPVC Column Pipes for Submersible Pumps



SAMUDRA PLATINUM

Parameters	Range
Product	1" to 5" (25 mm to 140 mm)
Classes	V4 (12.5 - 15.0 Kg) Medium, Standard & Heavy
Variant	Bell end & Coupler type

SALIENT FEATURES

- C-Ring locking system prevents the unlocking / loosening / Slippage of the pipes while in operation and during dismantling.
- Threads withstand considerable Shock, Jerk and pressure loads as well. Proper thread lengths with stoppage ensures its firmness.
- Coupler holds the successive pipes and makes the complete Pipe chain. Well designed couplers couples the pipes accurately and eliminating the misalignment between pipes.
- Specially Designed "Double Lip Sealing Rings" are provided on both permanent and temporary ends of the pipes.



Light
Weight



Energy
Saving



Cost
Effective



100%
Leak Proof
Joints



High Tensile
Strength

APPLICATIONS



Open Well



Bore Well

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore - 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255