

Single Phase | High Speed

# Horizontal Multi Stage Pressure Boosting System



▶ SPBS

\*Available in **NX** series

Parameters	Range
Power Rating	1.0 - 1.5 hp
Pressure Flow	2 - 4 Bar
Flow Rate	5 m <sup>3</sup> /hr
Pipe Size	30 / 25 X 25 mm
Voltage	240 V (-15% to +6%)
Speed	2850 rpm



## SALIENT FEATURES

- Energy efficient hydraulic & electric design
- TEFC, AC induction motor with "F" class winding for continuous operations
- High quality branded pressure switch & pressure tank
- 5-way connector ensure operation at wide demand range & this increasing product life
- Hydraulic component materials are made of high corrosion resistance stainless steel
- Rigid construction for noiseless operation & vibration free running

## APPLICATIONS



Pressure boosting system



Fountains, Lawns and Gardens



Large Multistoried Apartments

**SAMUDRA PUMPS (INDIA) PVT LTD**

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045. Tamilnadu, India

E-Mail: [info@samudrapumps.com](mailto:info@samudrapumps.com) | +91 422 498 2255

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice