

Three Phase

# Slow Speed Monobloc Pumpset



► SMS

\*Available in X series

Parameters	Range
Power Rating	3.0 - 7.5 hp
Head Range	3 - 14 m
Discharge Range	10 - 71 lps
Voltage	415 V (-15% to +6%)
Speed	1440 rpm



## SALIENT FEATURES

### MOTOR

- Three phase TEFC induction motor
- Dynamically balanced rotor
- All casing parts are FG 260 grade cast iron
- Suitable for 300V to 440V three phase, 50Hz power supply
- Large size bearing for better life

### PUMP

- All casing parts are FG 260 grade cast iron
- Stainless steel packing gland with SS steel studs
- Balanced impeller
- Brass impeller lock nuts
- Improve hydraulic performance

## APPLICATIONS



Sprinkler, Drip and Open Irrigation



Fountains, Lawns and Gardens



Water circulation system

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

**SAMUDRA PUMPS (INDIA) PVT LTD**

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045, Tamilnadu, India

E-Mail: [info@samudrapumps.com](mailto:info@samudrapumps.com) | +91 422 498 2255