

Three Phase I High Speed

Vertical Openwell Submersible Pumpset



► SVSM

*Available in X, NXC series

Parameters	Range
Power Rating	3.0 - 15 hp
Head Range	10 - 138 m
Discharge Range	3 - 19 lps
Voltage	415 V (-15% to +6%)
Speed	2850 rpm

SALIENT FEATURES

- Energy efficient motors and pumps
- Wide operating voltage band
- Robust design for better rigidity
- Increased water volume for better cooling
- Three layer protection to avoid sand entry into motor
- Increased life with high grade cast iron components - FG 260
- Superior construction for easy installation and easy serviceability
- Heavy duty water lubricated journal carbon bushes and thrust bearing for long trouble free operation
- Independent construction of pump & motor which is advantageable of pairing different stage of pumps with the same hp related motors



APPLICATIONS



Sprinkler, Drip and
Open Irrigation



Fountains, Lawns
and Gardens



Water supply in
apartments & buildings

In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255