

Single Phase

Vertical Submersible Pumpset



► SVS

*Available in X series

Parameters	Range
Power Rating	1.0 - 1.5 hp
Head Range	13 - 78 m
Discharge Range	30 - 180 lpm
Voltage	220 V (-15% to +6%)
Speed	2850 rpm

SALIENT FEATURES

- Easy installation & foundation not required
- Improved efficient and reduced power consumption
- Impellers and diffusers of high quality water portable engineering polymer
- Motor & pump is coupled with a slide coupling for easy serviceability
- Easy rewindable squirrel cage motor designed to operate in a wide range of voltage variation 180 - 240 V, 50 Hz power supply
- Pre - filled with special anti-corrosive solution to protect internal parts of motor from corrosion
- CED coated cast iron components for long lasting corrosion protection
- Special mounting stands are provided for placing the sets in horizontal position

OPERATING CONDITIONS

- Single Phase, 180 - 240V, 50Hz, AC power supply
- Protect to be earthed properly to avoid malfunction

APPLICATIONS



Sprinkler, Drip and Open Irrigation



Fountains, Lawns and Gardens



Water supply in apartments & buildings



Lifting water from sump to overhead tanks



In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore - 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255