

Three Phase I Radial Flow

# Borewell Submersible Pumpset (150 mm)



## ► SRS

\*Pumpsets available in **X**, **NX**, **N** & **NV** series also

	<b>X / NX series</b>	<b>N / NV series</b>
<b>Parameters</b>	<b>Range</b>	<b>Range</b>
Power Rating	3.0 - 25.0 hp	3.0 - 7.5 hp
Head Range	28 - 524 m	14 - 251 m
Discharge Range	18 - 450 lpm	18 - 450 lpm
Voltage	415 V (-15% to +6%)	350V (-15% to +6%)
Speed	2850 rpm	2850 rpm

## SALIENT FEATURES

- Energy efficient motors and pumps
- Wide operating voltage band
- All casting are in superior FG 260 grade
- Heavy duty journal and tilting thrust bearings
- Optimized diaphragm design
- Motor filled with anti-corrosive solution
- Easy serviceability
- Three layer protection to avoid sand entry into motor
- Pumps fitted with SS NRV
- Each stage is fitted with sand resisting rubber / rubber clad metal bushes

## APPLICATIONS



Water extract from borewells



Domestic & Community water supply



Cooling water circulation system & Water treatment system



In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

## SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045, Tamilnadu, India

E-Mail: [info@samudrapumps.com](mailto:info@samudrapumps.com) | +91 422 498 2255