

Three Phase I Radial Flow



SAMUDRA

Ultra Head Borewell Submersible Pumpset (165 mm)

► SRS UH

*Available in **X, NX** series

Parameters	Range
Power Rating	5.0 - 25.0 hp
Head Range	25 - 358 m
Discharge Range	30 - 600 lpm
Voltage	415 V (-15% to +6%)
Speed	2850 rpm

SALIENT FEATURES

- Energy efficient motors and pumps
- Wide operating voltage band
- All casting are in superior FG 260 grade
- Heavy duty journal and tilting thrust bearings
- Optimized diaphragm design
- Motor filled with anti-corrosive solution
- Easy serviceability
- Three layer protection to avoid sand entry into motor
- Pump bearing bush made up nitrile for better wear resistance
- Diffuser is made of IC casing CF grade & impeller is in CA 15 CA 40 grade steel

APPLICATIONS



Water extract from borewells



Domestic & Community water supply



Cooling water circulation system & Water treatment system



In View of continuous developments, the given information / descriptions / specifications are subject to change without prior notice

SAMUDRA PUMPS (INDIA) PVT LTD

Registered office: 1st Floor, Door No.737/2, Sai Aashrya, Puliyakulam Road, Coimbatore – 641 045, Tamilnadu, India

E-Mail: info@samudrapumps.com | +91 422 498 2255